

Winter tyre hassock

Pouffe made from a winter tyre

A high-profile stool

Disused winter tyres can now serve as a comfortable eye-catcher in your living room.



1 Introduction

Get off to a relaxing start this spring on your old winter tyres. But not on your car, in your home!

With the right materials and DIY skills, you can transform disused winter tyres into extraordinary high-profile stools. Painted in vibrant colours, these original seats create a unique effect in an apartment or on a balcony.

Required power tools:

- > PST 10,8 LI cordless multisaw
- > PFS 2000 paint spray system
- > PTK 3,6 LI cordless tacker

Other accessories:

- > Utility knife
- > Pencil
- > Nail
- > Parcel string

Detailed material list:

| pcs | Designation | Length | Width | Thickness Material |
|-----|-----------------------------------|--------|-------|--------------------|
| 1 | Old winter tyre | | | |
| 1 | Fabric | 50 cm | 50 cm | |
| 1 | MDF board | 50 cm | 50 cm | 8 mm |
| | Foam | 50 cm | 50 cm | 4 cm |
| | Paint | | | |
| | Turpentine for thinning the paint | | | |
| | Electric tacker staples | | | |



2 Painting

First clean the tyres. Then you can paint them in your favourite colour. You can do so evenly and easily with the PFS 2000 paint spray system. Then leave to dry thoroughly.

3 Measuring the seat

To ensure that the seat panel fits precisely in the tyre hole, measure the diameter of the hole and transfer it to the panel. This is easy to do with a nail and some string: Place the nail in the centre of the panel, fasten one end of the string to it at the length of the radius, tie the other end to the pencil and draw a circle.

4 Cutting out the seat panel

Now you can cut out the wooden panel, for example with the PST 10,8 LI cordless multisaw.

5 Cutting the foam to size

Cut the foam along the wooden panel using a utility knife. Then place the panel on the fabric and cut it out, leaving 7 cm extra on the edge.

6 Stapling together the seat

Now it's time for the cordless tacker, for example the PTK 3,6 LI: Centre the foam and the fabric on the wooden panel, turn everything over and staple the fabric to the panel. Place the stapled surface in the tyre. Your speedy seat is now finished!

Bosch does not accept any responsibility for the instructions stored here. Bosch would also like to point out that you follow these instructions at your own risk. For your own safety, please take all the necessary precautions.